


## FireKill Fire Hose Reel

55 Series



### FK-10

FK-10-A	25mm × 20mm
FK-10-B	25mm × 30mm

## 55 Series

Swinging hose reels are available in right and left hand formats suitable for surface or recess mounting.

55 Series hose reels are manufactured to LPCB EN 671-1:2001 and carry the CE mark notified body number 0832



New with pressure gauge

## Features

- Compact design with minimum protrusion
- Easy to maintain
- Fast "hose on" installation
- Supplied fully assembled
- Pressure gauge shows the pressure inside the hose reel
- Nozzle binding mechanical; not by clamp
- Wide range of sizes and capacities
- Automatic or manual versions



## FireKill Fire Hose Reel Tube EN 694 Certification

Model	Diameter	Maximum Working Pressure	Minimum Bursting Pressure	Deformation	Extension in Length	Adherence
Tube 25	25mm	12 Bar	42 Bar	<7.5%	<7.5%	>1.5kN/m

\* Tubing is supplied in 20m & 30m lengths as standard. Other lengths are available

### DESCRIPTION

Flexible Hose with Polyester Reinforcement

Color	Red (Black available subject to minimum quantity)
Outside Finish	Smooth (Corrugated available subject to minimum quantity)



EN694

### FireKill Hose Reel Accessories



RED NYLON NOZZLE (N -01)

Model	Inlet Pressure Bar	Hose Length & Diameter	Jet (LPM)	Spray (LPM)	Throw (per Meters)
N - 01	2	30m x 19mm	22	34	8.5
N - 01	2	30m x 25mm	28	50	10
N - 01	3	30m x 19mm	30	47	11
N - 01	3	30m x 25mm	37	67	12
N - 01	4	30m x 19mm	33	53	12
N - 01	4	30m x 25mm	44	78	13
N - 01	5	30m x 19mm	39	62	12
N - 01	5	30m x 25mm	51	86	14
N - 01	6	30m x 19mm	43	69	13
N - 01	6	30m x 25mm	55	95	16



Brass NOZZLE (N -09)

Model	Inlet Pressure Bar	Jet (LPM)	Spray (LPM)	Throw (Per Meters)
N - 09	2	38	78	11
N - 09	4	57	116	15
N - 09	6	70	143	18
N - 09	8	82	163	21
N - 09	10	88	183	22

\* Performance is based on pressure at nozzle not inlet pressure to reel.



CE EN671-1  
0832

